

GENERAL SPECIFICATIONS

Extremely broadband DC - 26.5 GHz
 Attenuation Values 3, 6, 10 & 20 dB standard
 VSWR (max):
 DC to 18.0 GHz 1.30
 18.0 to 26.5 GHz 1.40


Attenuation Accuracy:
 1 thru 6 dB ± 0.40 dB
 7 thru 20 dB ± 0.60 dB
 21 thru 30 dB ± 0.80 dB

RF Power 2 Watts average at +25 °C
 Nominal Impedance 50 Ohms
 Connectors 3.5 mm M/F
 (M/M & F/F available)

Material :
 Connectors & Housing Stainless Steel
 Center Conductors Gold Plated Beryllium Copper
 Temperature Range -55° C to +85° C



9454



Model 9454-Value in dB

CALIBRATED ATTENUATOR SETS



Model A954 3.5 mm Connectors

GENERAL SPECIFICATIONS

Frequency Range DC to 26.5 GHz
 Attenuation Values 3, 6, 10, & 20 dB
 Calibration Points (GHz) DC, 2.0, 4.0, 8.0,
 12.4, 18.0 & 26.5

Each set is conveniently packaged in a fitted carrying case with the calibration chart attached to the inside cover. All measurements are traceable to the National Institute of Standards and Technology.